

AUSEAL PTY LTD

SAME DAY SEAL

SAME DAY SEAL is a concrete sealant specifically formulated for sealing and protecting freshly poured (sufficiently hard able to be walked on) green concrete surfaces. An additional coat of **AUSEAL – EC25** is recommended for optimum performance. **SAME DAY SEAL** is based on 100% acrylic copolymer.

FEATURES

- ☐ Excellent durability – good UV stability
- ☐ Excellent Water Resistance
- ☐ Reduces Efflorescence
- ☐ Suitability for both Interior and Exterior application.
- ☐ Low tyre marking characteristics
- ☐ Good abrasion resistance
- ☐ Curing aid for Concrete.

COLOUR RANGE: Available in Clear.

APPLICATION: Suitable for application by broom, roller or airless spray to freshly poured concrete.

COVERAGE: 5 – 7 Square metres per litre depending on profile and porosity of surface.

SPECIFICATION:

Application Temperature	min. 8 deg C max.28 deg C
Recoat Time	Min. 24 Hrs – 28 Days
Full Film Formation (Cure)	7 Days.

PACKAGING AND SAFETY: **SAME DAY SEAL** is available in 10, 20 and 200 litre drums.
Refer to the Material Safety Data Sheet before handling or use.

AUSEAL PTY. LTD. – Manufacturers and Suppliers of Protective and Decorative Sealants and Coatings to the Concrete Industry.

25 – 29 Pelson Court (P.O. Box 441) Dandenong 3175.
Tel: (03) 8787 8388 Fax: (03) 8787 8366 Email: info@auseal-curite.com.au

DIRECTIONS FOR SURFACE PREPARATION AND APPLICATION

SURFACE PREPARATION

All surfaces to be sealed or coated must be free from dust, dirt, oil, grease and other contaminants.

APPLICATION

Stir thoroughly before and during application to ensure uniformity, making sure that any suspended pigment (if coloured) is completely re-incorporated.

Apply coating **evenly** with broom, roller or spray gun. Uneven application may result in blistering.

Allow recommended drying time and apply evenly one full **second coat** without dilution 7 – 28 days.

CLEANING

SAME DAY SEAL can be removed from tools and equipment with Auseal-Curite Solvent.

PRECAUTIONS

1. **SAME DAY SEAL IS A COMBUSTIBLE LIQUID.**
2. Provide adequate ventilation during application and drying.
3. Store away from naked flames and sparks.
4. Ensure you are familiar with MSDS prior to usage.

AUSEAL PTY. LTD. – Manufacturers and Suppliers of Protective and Decorative Sealants and Coatings to the Concrete Industry.

25 – 29 Pelson Court (P.O. Box 441) Dandenong 3175.

Tel: (03) 8787 8388 Fax: (03) 8787 8366 Email: info@auseal-curite.com.au